



NOTE:

1. CABLE: 28AWG X 8C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02)
PVC JACKET $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS.UL RECOGNIZED.
P2:D-SUB 25PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS.UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.
7. EACH ONE WITH TWO #4-40 UNC SCREW.

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV A
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	02/10/11		
TITLE	DB25M TO DB9F		
PART NO.	NMJ-98-020411W-02M		